

IRIDIUM Sirius Plexi

RF Mono-Antenna System 8,2 MHz for tags and paper labels.

Frequency: 8,2 MHz RF Weight: 17,5 kg

Power supply: 15V AC included in delivery mono, luxury design

Construction: very strong

Material: transparent plexiglass thickness 20mm,

width 396mm, stainless box and base plate with scotch brite surface, plexiglass manufacturer guarantees 30-years

warranty against yellowing Alarm sound: small piezo, 100dB loudness

Alarm light: red colour LED

Optional facility: blue lighting during operation

of system

General information:

- Easy to install. It is real "plug & play" mono system, no setup needed
- It is possible to synchronize unlimited number of systems (by wire)
- Possible automatic synchronization up to 6 systems (by air)
- Automatically detects network frequency (50Hz, or 60Hz)


Electronics:

- Real time signal processing and SMD technology
- It detects close by "standing tags" and signalizes it to the staff
- DC version is available, because of very low power consumption. The el. power is consumed by a system functioning, not to heat (the maximum part temperature is 35°C only)
- It is covered with thin metal cover. It is also for noise protection and unauthorized acts prevention. All important information are printed on the cover.
- Very simple and easy to replace (a few seconds)
- Automatically adjusts the parameters for optimal detection of tags
- The system detection tree is flat and possible to adapt according a customer requirement.
- Transmitting frequency is automatically shifting from 7,8MHz to 8,5MHz with steps of 100kHz and accuracy of up to 6kHz. It detects all type of RF 8,2 MHz tags and labels. There is no additional tuning needed.

Detection distances table:

Paper labels 3 x 4 cm	2 x 0,7 - 0,8 m
Paper labels 4 x 4 cm	2 x 0,8 - 0,9 m
Paper labels 5 x 5 cm	2 x 0,9 - 1,0 m
Hard tag D50	2 x 1,15 - 1,2 m
Hard tag D40	2 x 1,0 - 1,1 m
Hard tag Mini square	2 x 1,0 - 1,1 m

Warranty: 3 years



Drawings and technical information of this data sheets issued for marketing purposes only and may not be reproduced or used to manufacture anything shown or referred to hereon without permission from IRIDIUM LTD



Hraničná 12, 058 01 POPRAD Slovakia



tel.: 00421 52 7721 210 fax: 00421 52 7728 730, 7721360 email: info@iridiumltd.sk



